

- DP-920G** ■ MODEL  
 ■ DP-920G-Standard Version.....標準型  
     MT3# Spindle .....MT3# 主軸  
     Forward and reverse tapping system.....攻牙系統  
 ■ DP-920GC-CE Standard Version .....CE 標準型

SPECIFICATIONS 規格表		DP-920G	
DRILLING CAPACITY 最大鑽孔能力	Steel	MT3 32 mm MT4 40 mm	1-1/4" 1-1/2"
TAPPING CAPACITY 最大攻牙能力		19 mm	3/4"
SWING 主軸旋徑		530 mm	20.8"
SPINDLE TAPER 主軸錐度		MT3# , MT4#	
SPINDLE TRAVEL 主軸行程		150 mm	6"
QUILL DIAMETER 主軸直徑		75 mm	3"
COLUMN DIAMETER 立柱直徑		115 mm	4-1/2"
SPINDLE NOSE TO TABLE 主軸至工作台最大距離		925 mm	36.4"
SPINDLE NOSE TO BASE 主軸至底座最大距離		1225 mm	48"
TABLE SIZE(L x W) 工作台尺寸(長x寬)		560 x 470 mm	22" x 18.5"
TABLE SLOT 工作台型槽		16 mm	5/8"
BASE SIZE(L x W) 底座尺寸(長x寬)		685 x 485mm	27" x 19"
SPINDLE SPEED 主軸速度		High:245 ~ 2000 rpm 高速 Low:65 ~ 540 rpm 低速	
MOTOR 馬達		2 HP / 3 PH	
COOLANT MOTOR 冷卻馬達		1/8HP / 3 PH	
MACHINE SIZE(L / W / H) 機器尺寸(長 / 寬 / 高)		1085 x 578 x 2035 mm 42.7" x 22.7" x 80"	
NET WEIGHT 淨重		340 kgs	
MEASUREMENT 材積		42 CU.FT.	

