

DP-925GAD

- MODEL
- DP-925GAD-Standard Version.....標準型
 - MT4# SpindleMT4# 主軸
 - Forward and reverse tapping system.....攻牙系統
 - Digital tachometer display速度顯示器
 - Coolant System.....冷卻系統
- DP-925GAC-CE Standard Version.....CE 標準型

SPECIFICATIONS 規格表		DP-925GAD	
DRILLING CAPACITY 最大鑽孔能力	Steel	40 mm	1-1/2"
	Cast iron	45 mm	1-3/4"
TAPPING CAPACITY 最大攻牙能力		24 mm	16/15"
SWING 主軸旋徑		530 mm	20.8"
SPINDLE TAPER 主軸錐度		MT4#	
SPINDLE TRAVEL 主軸行程		150 mm	6"
QUILL DIAMETER 主軸直徑		75 mm	3"
COLUMN DIAMETER 立柱直徑		115 mm	4-1/2"
SPINDLE NOSE TO TABLE 主軸至工作台最大距離		580 mm	22.75"
SPINDLE NOSE TO BASE 主軸至底座最大距離		1135 mm	40.75"
TABLE SIZE(L x W) 工作台尺寸(長x寬)		560 x 470 mm	22" x 18.5"
TABLE SLOT 工作台T型槽		16 mm	5/8"
BASE SIZE(L x W) 底座尺寸(長x寬)		685 x 485 mm	27" x 19"
SPINDLE SPEED 主軸速度		High:245 ~ 2000 rpm 高速 Low:65 ~ 540 rpm 低速	
AUTOMATIC QUILL FEEDS 自動進刀速度		3 speeds(段) 0.2 , 0.1 , 0.05(mm) Per Revolution	
MOTOR 馬達		2 HP / 3 PH	
COOLANT MOTOR 冷卻馬達		1/8HP / 3 PH	
MACHINE SIZE(L / W / H) 機器尺寸(長 / 寬 / 高)		872 x 580 x 2000 mm 34.3" x 22.8" x 78.7"	
NET WEIGHT 淨重		385 kgs	
MEASUREMENT 材積		49.7 CU.FT.	

Spindle auto
down feed.
主軸自動進刀



■ Automatic down feed speed changer.
自動進刀變速