

### DP-915AH

- MODEL
- DP-915AH - Standard Version ..... 標準型  
 MT3# Spindle ..... MT3# 主軸  
 Tapping system ..... 攻牙系統  
 Digital tachometer ..... 速度顯示器
- DP-915AHE - CE Standard Version ..... CE 標準型

SPECIFICATIONS 規格表		DP-915AH	
DRILLING CAPACITY 最大鑽孔能力	Steel Cast iron	25 mm 32 mm	1" 1-1/4"
TAPPING CAPACITY 最大攻牙能力	Steel Cast iron	16 mm 19 mm	5/8" 3/4"
SWING 主軸旋徑		408 mm	16"
SPINDLE TAPER 主軸錐度			MT3#
SPINDLE TRAVEL 主軸行程		135 mm	5.3"
QUILL DIAMETER 主軸直徑		62 mm	2-7/16"
COLUMN DIAMETER 立柱直徑		92 mm	3.6"
SPINDLE NOSE TO TABLE 主軸至工作台最大距離		605 mm	23.8"
SPINDLE NOSE TO BASE 主軸至底座最大距離		1150 mm	45.3"
TABLE SIZE (L x W) 工作台尺寸(長 x 寬)		460 x 360 mm	18.1" x 14.2"
TABLE SLOT 工作台T型槽		16 mm	5/8"
BASE SIZE (L x W) 底座尺寸(長 x 寬)		685 x 485 mm	27" x 19"
SPINDLE SPEED 主軸速度		150 ~ 3000 rpm	
MOTOR 馬達		2 HP/ 1 PH or 3 PH	
COOLANT MOTOR 冷卻馬達		1/8HP	
MACHINE SIZE (L x W x H) 機器尺寸(長 x 寬 x 高)		660 x 460 x 1765 mm 26" x 18" x 69.5"	
NET WEIGHT/GROSS WEIGHT 淨重 / 毛重 kgs		220/260	
PACKING SIZE (L x W x H) 裝箱尺寸(長 x 寬 x 高)		820 x 610 x 2000 mm 32.3" x 24" x 78.8"	34.3 CU.FT.

- Variable spindle speed 150~3000rpm.  
無段轉速150~3000rpm
- Variable speed inverter technology for easier control.  
無段變頻器系統，操作方便
- Able to perform drilling and tapping functions.  
可鑽孔及攻牙

